## IN THE CLAIMS:

Claims 1-87 (Canceled).

88. (Currently Amended) A snowplow blade mount assembly mountable on a vehicle comprising a frame mount assembly, a support assembly, and a plow mount assembly, said frame mount assembly designed to be substantially non-detachably mountable to a frame at a front end of the vehicle without connection to a front bumper of the vehicle, said support mount assembly designed to at least partially support a lift mount assembly devised to at least partially lift at least a portion of said plow mount assembly, said plow mount assembly including a frame structure designed to be connected to a snowplow blade at one end and said support mount assembly at another end, said frame mount assembly positioned substantially below a bottom level of the front bumper, and behind a front surface of the front bumper, and substantially fully positioned under the front end of the vehicle when mounted to the vehicle, said support assembly detachably connected to a connection arrangement of said frame mount assembly, said connection arrangement at least partially positioned below the bottom level of the front bumper and substantially positioned under the front end of the vehicle when said frame mount assembly is mounted to said vehicle, said connection arrangement fully securing said support assembly to said frame mount assembly, said connection arrangement including a plurality of connectors, at least two of said connectors connecting said support assembly to said frame mount assembly, said connection arrangement including at least one engagement arrangement that receives at least a part of a front portion of said support assembly and at least partially limits movement of said support assembly relative to said fame frame mount assembly when said support assembly is secured by said connection arrangement, at least one of said connectors is spaced forwardly from said engagement arrangement, said plow mount assembly pivotally connected connectable to said support assembly and spaced forwardly from said frame mount assembly when said support assembly is connected to said frame mount assembly and said frame mount assembly is connected to said support assembly, said plow mount assembly detachably connectable to said support assembly to enable said plow mount assembly to be disengaged from the vehicle without having to partially or fully disconnect said support assembly from said frame mount assembly.

- 89. (Currently Amended) The assembly as defined in claim 88, wherein said at least one engagement arrangement of said connection arrangement designed to <u>at least partially</u> telescopically receive at least a portion of said support assembly.
- 90. (Previously Presented) The assembly as defined in claim 88, wherein a portion of said at least one engagement arrangement includes an angular lip to guide at least a portion of said support assembly when connecting said support assembly to said frame mount assembly.
- 91. (Previously Presented) The assembly as defined in claim 89, wherein a portion of said at least one engagement arrangement includes an angular lip to guide at least a portion of said support assembly when connecting said support assembly to said frame mount assembly.
- 92. (Currently Amended) The assembly as defined in claim 88, wherein said connection arrangement includes first and second connectors to at least partially secure said support assembly to said frame mount assembly, said first connector at least partially positioned in said at least one engagement arrangement said and second connector connectors spaced from said at least one

engagement arrangement.

- 93. (Currently Amended) The assembly as defined in claim 91, wherein said connection arrangement includes first and second connectors to at least partially secure said support assembly to said frame mount assembly, said first connector at least partially positioned in said at least one engagement arrangement said and second connector connectors spaced from said at least one engagement arrangement.
- 94. (Currently Amended) The assembly as defined in claim 92, wherein said <u>first and</u> second connectors <del>connector includes</del> a <u>include</u> removable <del>pin</del> <u>pins</u>.
- 95. (Currently Amended) The assembly as defined in claim 93, wherein said <u>first and</u> second connectors <del>connector includes a include</del> removable <del>pin</del> pins.

Claims 96-99 (Canceled).

- 100. (Currently Amended) The assembly as defined in claim 88, wherein said plow mount assembly includes including a leg support to elevate at least one end of said plow mount assembly from the ground when said plow mount assembly is detached separated from said vehicle.
- 101. (Currently Amended) The assembly as defined in claim 95, wherein said plow mount assembly includes including a leg support to elevate at least one end of said plow mount assembly from the ground when said plow mount assembly is detached separated from said vehicle.

- 102. (Previously Presented) The assembly as defined in claim 100, wherein said leg support adjustably elevates said at least one end of said plow mount assembly from the ground.
- 103. (Previously Presented) The assembly as defined in claim 102, wherein said leg support is positionable between a retracted non-supporting position and an extended supporting position.
- 104. (Currently Amended) The assembly as defined in claim 88, including a wherein said lift mount assembly secured to said support assembly is detachably connected to said plow mount assembly.
- 105. (Currently Amended) The assembly as defined in claim 101, including a wherein said lift mount assembly secured to said support assembly is detachably connected to said plow mount assembly.
- 106. (Currently Amended) The assembly as defined in claim 104 88, wherein said lift mount assembly is permanently rigidly connected to said support assembly.
- 107. (Currently Amended) The assembly as defined in claim 104 88, wherein said lift mount assembly includes first and second extension legs, said legs including a plurality of connector positions to adjustably position the height of a lift bar connected to said legs.
  - 108. (Previously Presented) The assembly as defined in claim 105, wherein said lift mount

assembly includes at least one auxiliary light connector designed to connect an auxiliary light to said lift mount assembly.

- 109. (Currently Amended) The assembly as defined in claim 104 88, wherein said lift mount assembly includes including at least one auxiliary light connector designed to connect an auxiliary light to said lift mount assembly.
- 110. (Currently Amended) The assembly as defined in claim 88, including a snowplow blade connected to said plow mount assembly, wherein said snowplow blade includes a flexible deflector flap secured to a top edge of said plow blade and extending downwardly from said top edge.
- 111. (Currently Amended) The assembly as defined in claim 108, including a snowplow blade connected to said plow mount assembly, wherein said snowplow blade includes a flexible deflector flap secured to a top edge of said plow blade and extending downwardly from said top edge.
- 112. (Previously Presented) The assembly as defined in claim 88, wherein said plow mount assembly includes a skid plate designed to contact a ground surface when plowing snow from the ground surface, said skid plate adjustably extendable toward said ground surface.
- 113. (Previously Presented) The assembly as defined in claim 111, wherein said plow mount assembly includes a skid plate designed to contact a ground surface when plowing snow from

the ground surface, said skid plate adjustably extendable toward said ground surface.

114. (Previously Presented) A snowplow blade mount assembly mountable on a vehicle comprising a frame mount assembly having a connection arrangement, a support assembly having a connection end, and a plow mount assembly having including a frame structure that is designed to be connected to said support mount assembly at a support connection end and a snowplow blade at a plow connection end, said support mount assembly designed to at least partially support a lift mount assembly that is devised to at least partially lift said plow mount assembly, said frame mount assembly designed to be substantially non-detachably mountable to a frame at a front end of the vehicle without connection to a front bumper of the vehicle, said frame mount assembly positioned substantially below a bottom level of the front bumper, and behind a front surface of the front bumper, and substantially fully positioned under the front end of the vehicle when mounted to the vehicle, said connection end at a front portion of said support assembly detachably connected to the connection arrangement of said frame mount assembly, said connection arrangement at least partially positioned below the bottom level of the front bumper and substantially positioned under the front end of the vehicle, said connection arrangement fully securing said support assembly to said frame mount assembly, said connection arrangement including at least one engagement arrangement and a plurality of connectors positioned forwardly of the at least one engagement arrangement, at least two of said connectors connecting said support assembly to said frame mount assembly, said at least one engagement arrangement designed to receive at least a part of the front portion of said support assembly and to at least partially limit movement of said support assembly relative to said fame frame mount assembly when said support assembly is secured by said connection arrangement, said plow mount assembly including a leg support designed to elevate said support connection end at least a portion of said plow mount assembly from a ground surface when said connection end of said support assembly is detached from said connection arrangement of said frame mount assembly while said plow mount is connected to said support assembly or when said support connection end is detached from said support assembly, said support connection end of said plow mount assembly pivotally connected connectable to said support assembly and spaced forwardly from said connection arrangement of said frame mount assembly when said support assembly is connected to said frame mount assembly, said plow mount assembly detachably connectable to said support assembly to enable said plow mount assembly to be disengaged from the vehicle without having to partially or fully disconnect said support assembly from said frame mount assembly.

115. (Currently Amended) The assembly as defined in claim 114, wherein said leg support adjustably elevates said connection end at least a portion of said snow plow mount assembly from the ground.

Claim 116 (Canceled).

- 117. (Previously Presented) The assembly as defined in claim 115, wherein said leg support is positionable between a retracted non-supporting position and an extended supporting position.
- 118. (Previously Presented) The assembly as defined in claim 114, wherein said plurality of connectors each include at least one removable pin.

119. (Previously Presented) The assembly as defined in claim 117, wherein said plurality of connectors each include at least one removable pin.

Claim 120 (Canceled).

- 121. (Previously Presented) The assembly as defined in claim 118, wherein at least one of said removable pins is secured in position by a removable pin clip.
- 122. (Previously Presented) The assembly as defined in claim 119, wherein at least one of said-removable pins is secured in position by a removable pin clip.

Claim 123 (Canceled).

- 124. (Previously Presented) The assembly as defined in claim 114, wherein said support connection end of said plow mount assembly is detachably connected to said support assembly by at least one removable pin.
- 125. (Previously Presented) The assembly as defined in claim 122, wherein said support connection end of said plow mount assembly is detachably connected to said support assembly by at least one removable pin.

Claim 126 (Canceled).

127. (Previously Presented) The assembly as defined in claim 124, wherein at least one of said removable pins is secured in position by a removable pin clip.

128. (Previously Presented) The assembly as defined in claim 125, wherein at least one of said removable pins is secured in position by a removable pin clip.

Claims 129-132 (Canceled).

133. (Previously Presented) The assembly as defined in claims 114, wherein said connection arrangement includes at least two engagement arrangements, each of said engagement arrangement is designed to at least partially telescopically receive at least a portion of said support assembly.

- 134. (Previously Presented) The assembly as defined in claims 128, wherein said connection arrangement includes at least two engagement arrangements, each of said engagement arrangement is designed to at least partially telescopically receive at least a portion of said support assembly.
- 135. (Currently Amended) The assembly as defined in claim 132 121, wherein said connection arrangement includes at least two engagement arrangements, each of said engagement arrangement is designed to at least partially telescopically receive at least a portion of said support assembly.

Claim 136 (Canceled).

- 137. (Currently Amended) The assembly as defined in claim 114, including a wherein said lift mount assembly secured to said support assembly is detachably connected to said plow mount assembly.
- 138. (Currently Amended) The assembly as defined in claim 137128, including a wherein said lift mount assembly secured to said support assembly is detachably connected to said plow mount assembly.
- 139. (Currently Amended) The assembly as defined in claim 114, said lift mount assembly includes including at least one auxiliary light connector designed to connect an auxiliary light to said lift mount assembly.
- 140. (Currently Amended) The assembly as defined in claim 114, including a wherein said snowplow blade is detachably connected to said plow connection end of said plow mount assembly.
- 141. (Currently Amended) The assembly as defined in claim 134, including a wherein said lift mount assembly secured to said support assembly is detachably connected to said plow mount assembly.
- 142. (Currently Amended) The assembly as defined in claim 141 138, wherein said lift mount assembly includes including at least one auxiliary light connector designed to connect an

auxiliary light to said lift mount assembly.

- 143. (CurrentlyAmended) The assembly as defined in claim 142, including a wherein said snowplow blade is detachably connected to said plow connection end of said plow mount assembly.
- 144. (Currently Amended) The assembly as defined in claim 114, wherein said plow mount assembly is spaced <u>forwardly</u> from said frame assembly when said support assembly is <u>pivotally</u> connected to said frame mount assembly and said frame mount assembly is connected to said support assembly.
- 145. (Currently Amended) The assembly as defined in claim 143, wherein said plow mount assembly is spaced <u>forwardly</u> from said frame assembly when said support assembly is <u>pivotally</u> connected to said frame mount assembly and said frame mount assembly is connected to said support assembly.